



	Type 1				Type 2		
	41645-67	43282-00A	41690-67	43315-00A	42301-00	34926-52	34927-52
Pression d'utilisation Working Pressure	0-345 bar	0-345 bar	0-345 bar	0-345 bar	0-250 bar	0-250 bar	0-250 bar
A	39,7	39,7	39,7	39,7	40,5	40,5	40,5
B	26	26	26	26	29,3	29,3	29,3
C	9,1	9,1	9,1	9,1	7,2	7,2	7,2
D	1,8Max	1,8Max	1,8Max	1,8Max	0,6	0,6	0,6
Mécanisme Core	---	---	---	---	29112-06	29112-06	---
Bouchon Cap	32069-01 nickelé <i>nickel plated</i>	32069-01 nickelé <i>nickel plated</i>	28718-57 jaune <i>yellow</i>	28718-57 jaune <i>yellow</i>	28718-57 jaune <i>yellow</i>	28718-54 bleu <i>blue</i>	28718-54 bleu <i>blue</i>
Norme Standard	---	---	MS28889-2	M6164-5	AN-6287	AN-6287	AN-6287
Commentaire Comment	Compatible avec liquide hydraulique Skydrol 500A <i>Compatible with Skydrol 500 A hydraulic fluid</i>	Compatible avec liquide hydraulique NSA307110 <i>Compatible with NSA 307110 hydraulic fluid</i>					

Echelle 1/ scale 1

